



The new L-Shaped steel edging, Flexibility with a robust edge.

Halestem is a new product from EverEdge that has been specifically designed to offer a flexible solution for straight lines or curves where an L-shape edge is required.

Made from galvanised steel, the 6mm rolled top edge guarantees a robust product that is ideal for use with asphalt/tarmac, resin bonded surfaces, blocks, paving and driveways.

Coming in two versions, it allows buyers to select either the rigid option for straight lines or a flexible alternative to work with curved borders. Separate corner sections are also available to form 90 degree bends, ensuring a neat and unified finish.

- Quick and easy to install
- 2mm thick edging can be laid to suit any design
- Comes with 5 anchor pins per strip

| Code | Height (mm) | Rigid/Flexible | Thickness (mm) |
|----------|-------------|----------------|----------------|
| HST50/R | 50 | RIGID | 2 |
| HST50/F | 50 | FLEXI | 2 |
| HST75/R | 75 | RIGID | 2 |
| HST75/F | 75 | FLEXI | 2 |
| HST100/R | 100 | RIGID | 2 |
| HST100/F | 100 | FLEXI | 2 |
| HST150/R | 150 | RIGID | 2 |
| HST150/F | 150 | FLEXI | 2 |

Typical Usage

- Asphalt/Tarmac
- Resin Bonded Surfaces
- Blocks, Paving &
- Driveways



Technical Data

| | |
|---------------------|-------------------------------------|
| Current Size Range | 50-150mm |
| Steel thickness | 2.0mm high tensile galvanised steel |
| Length | 2.5 metres |
| Steel specification | BSEN 10346-2015 DX51 D+Z |
| Tensile Strength | 270 to 500 N/mm ² |
| Roll-top | 6 x 10mm |
| Types | Flexi and rigid |
| Anchor Pins | 5 x 2.5 metres, 7 x 200mm spiralled |