



For larger edging projects, flexible galvanised ProEdge is the Professional's choice for a clean continuous edge.

ProEdge is 2.5 metres long and 2.5 mm thick and comes in heights of 75, 100, 125 and 150mm. All sizes are interchangeable except DP1. The spike lengths are 100mm.

Interlocking lengths of edging are installed using a wooden/ rubber/plastic mallet. ProEdge is quick and easy to install. The edging curves and also bends easily to any required angle. The 15 concave spikes per length fix the edging securely. In loose or stony ground, the "Pin and Sleeve" accessory may be required. Concrete (spot) haunching can be used if necessary.

ProEdge is used against all surfaces including: (hot) asphalt, stone, gravel, rubberised or resin bonded surfaces, brick and grass.

Code	Length (mm)	Thickness (mm)	Depth (mm)
AP1	2500	2.5	75
BP1	2500	2.5	100
CP1	2500	2.5	125
DP1	2500	2.5	150

Supplied in single lengths.

ProEdge lawn edging overlaps and interlocks, please remember to add 3% to your actual linear requirement.

Galvanising Specification

EverEdge ProEdge is manufactured to BS EN 10346-2009 with an average 20 micron zinc coating.

Typical Usage

- Parks
- Driveways
- Golf Clubs
- Memorial gardens
- Play areas
- Private gardens



Poor ground conditions? Use the Pin and Sleeve support.



M8 Coach Bolt used for extra strength on 150mm ProEdge DP1.

Colours Available

-  Brown
-  Slate
-  Unpainted
-  Cor-Ten®



For technical advice and sales call 01630 417120 or visit www.everedge.co.uk